




## TYPICAL ISOMETRICS



# **TYPICAL SECTIONS**





# **PROFILES**

1-5/8" X 2", 4", 6", 8" HD 2" X 2", 4", 6", 8" 4"x4", 4"x6" Standard lengths: 24'

## **COMPONENTS**

End Caps, Mounting Clips & Isolation Washers.

### ATTACHMENT

Fasten w. #12 screws\*(#14 for HD) @ 6' o.c. using Mounting Clips & Isolation Washers. (\*Not included)

\( \text{\Delta} \) See install guide for details.

#### **FINISHES**

Woodgrains, solid colors, naturally aged metals, special order. Custom solid color matching available (additional lead times apply).

#### BIM & CAD

RVT & DWG files available, see our website for details.

### **LEAD TIME**

Most Popular Finishes
-ready to ship within 1 week
Additional Finishes
-ready to ship within 14 weeks



info@longboardproducts.com longboardproducts.com 800 604 0343

ICS\_BAFFLE\_IS\_RF\_V7

## TECHNICAL SPECIFICATIONS

### PHYSICAL DATA

6063-T5 Extruded Aluminum

100% Recyclable

Warranty: Finish:15 year (standard)/20 year\* (ultra) (\*10 week lead time);

Aluminum: 50 year Dimensions/Weights:

L&L	Width	Depth	Length	Weight(lbs/LF) *per set
2"	2" (50.8mm)	1 5/8" (41.3mm)	12'/24'	0.93
4"	4" (101.6mm)	1 5/8" (41.3mm)	12'24'	1.3
6"	6" (152.4mm)	1 5/8" (41.3mm)	12'/24'	1.6
8"	8" (203mm)	1 5/8" (41.3mm)	12'/24'	1.9
4"x4"	4" (101.6mm)	4" (101.6mm)	12'/24'	1.8
4"x6"	6" (152.4mm)	4" (101.6mm)	12'/24'	2.1
4" HD	4" (101.6mm)	2° (50.8mm)	12'/24'	1.7
6" HD	6" (152.4mm)	2" (50.8mm)	12'/24'	2.4
8" HD	8" (203mm)	2" (50.8mm)	12'/24'	3

#### **TESTING**

ICC-ESR 4183 Evaluation Report - Division: 05 00 00 - METALS

· Section: 05 50 00 - Metal Fabrications

CAN/ULC S102

CAN/ULC S114

LARR - Los Angeles Department of Building Safety (LADBS) accepts ICC-ES reports as proof of compliance

WUI (The Wildland-Urban Interface) – California Department of Forestry & Fire Protection Office of the State Fire Marshal Listing No. 8140-2286:0500



Fire Rating: Class A Non-Combustible by ASTM E136 & ASTM E84



Acoustical Rating with insulation: NRC up to 0.80



Light reflectance (LRV): Up to 73.2% (Ultra White)