

TYPICAL ISOMETRICS



PROFILES

1-5/8" X (2", 4", 6", 8") HD 2" X (4", 6", 8") 4"x4", 4"x6" Standard lengths: 24'

COMPONENTS


End Caps, End Mounts, Mounting Clips & Isolation Washers.


ATTACHMENT

Fasten w. #12 screws*(#14 for HD) @ 6' o.c. using End Mounts, Mounting Clips & Isolation Washers (*Not included)

See install guide for details.

TYPICAL SECTIONS





LONGBOARD®

FINISHES

Woodgrains, solid colors, naturally aged metals, special order. Custom solid color matching available (additional lead times apply)

BIM & CAD

RVT & DWG files available, see our website for details.

LEAD TIME

Most Popular Finishes -ready to ship within 1 week Additional Finishes

-ready to ship within 14 weeks

info@longboardproducts.com longboardproducts.com 800 604 0343

L&L_S&P_IS_RE_V5

TECHNICAL SPECIFICATIONS

PHYSICAL DATA

6063-T5 Extruded Aluminum

100% Recyclable

Warranty: Finish:15 year (standard)/20 year* (ultra) (*10 week lead time);

Aluminum: 50 year Dimensions/Weights:

L&L	Width	Depth	Length	Weight(lbs/LF) *per set
2"	2" (50.8mm)	1 5/8" (41.3mm)	12'/24'	0.93
4"	4" (101.6mm)	1 5/8" (41.3mm)	12'24'	1.3
6"	6" (152.4mm)	1 5/8" (41.3mm)	12'/24'	1.6
8"	8" (203mm)	1 5/8" (41.3mm)	12'/24'	1.9
4"x4"	4" (101.6mm)	4" (101.6mm)	12'/24'	1.8
4"x6"	6" (152.4mm)	4" (101.6mm)	12'/24'	2.1
4" HD	4" (101.6mm)	2" (50.8mm)	12'/24'	1.7
6" HD	6" (152.4mm)	2" (50.8mm)	12'/24'	2.4
8" HD	8" (203mm)	2" (50.8mm)	12'/24'	3

TESTING

ICC-ESR 4183 Evaluation Report - Division: 05 00 00 - METALS

Section: 05 50 00 - Metal Fabrications

LARR - Los Angeles Department of Building Safety (LADBS) accepts ICC-ES reports as proof of compliance

Florida Building Code - Building

Florida Building Code - Residential

WUI (The Wildland-Urban Interface) – California Department of Forestry & Fire Protection Office of the State Fire Marshal Listing No. 8140-2286:0500



Fire Rating: Class A Non-Combustible by ASTM E136 & ASTM E84



Light reflectance (LRV): Up to 73.2% (Ultra White)