


# TYPICAL ISOMETRICS



# SINGLE POST









**BEAM END CAP** 

# **PROFILES**

1x3", 1x5" - Standard Lengths: 24'

## COMPONENTS

Single Post, -Standard 24'L Beam End Cap, Post End Cap - (20pcs) Spacer Bar (1", 12'), Spacer Block (100pcs) Mounting Bracket - (100pcs)

# **FINISHES**

Woodgrains, solid colors, naturally aged metals, special order. Custom solid color matching available (additional lead times apply).

# **ATTACHMENT**

Floating System attached with Mounting Brackets, End Frame System placed in posts and supported with Spacer Blocks

Spacer Bar - comes in 12ft lengths -cut for variable heights Spacer Block - 1-1/2" spacer

#### BIM & CAD

RVT & DWG files available, see website for details

### **LEAD TIME**

Most Popular Finishes -ready to ship within 1 week Additional Finishes -ready to ship within 14 weeks



info@longboardproducts.com longboardproducts.com 800 604 0343

# TECHNICAL SPECIFICATIONS

#### PHYSICAL DATA

6063-T5 Extruded Aluminum

100% Recyclable

Warranty: Finish:15 year (standard)/20 year\* (ultra) (\*10 week lead time);

Aluminum: 50 year

Weight (lbs/lf): 0.7 (1X3); 1.1 (1X5)

#### **TESTING**

ICC-ESR 4183 Evaluation Report - Division: 05 00 00 - METALS

• Section: 05 50 00 - Metal Fabrications

LARR - Los Angeles Department of Building Safety (LADBS) accepts ICC-ES reports as proof of compliance

Florida Building Code: Building Florida Building Code: Residential

WUI (The Wildland-Urban Interface) - California Department of Forestry & Fire Protection Office of the State Fire Marshall Listing No. 8140-2286:0500



Fire Rating: Class A Non-Combustible by ASTM E136 & ASTM E84



Light reflectance (LRV): 5% (Black) Up to 73.2% (Ultra White)