
PANELBOARD TM INTERIOR WALL SYSTEM

TYPICAL ISOMETRIC



PROFILES

Smooth: 6"

Standard Lengths: 24'


96 SQ FT/box

COMPONENTS - Standard Lengths: 12'

Traditional: 2" Corner Set, 1-3/8" Two Piece J-Track, 1-3/8" Termination Set, Compression Joint (24'), 1-1/2" Flat Reveal Set, 1-1/2" U-Reveal Set, 1-1/2" T&G U-Reveal

Craftsman: 3/4" Inside Corner, 1" Outside Corner, 3/4" U-Reveal Set, 3/4" T&G U-Reveal

Precision: 5/8" Starter J-Track, 3/16" Outside Corner, 5/8" J-Track, 5/8" Two Piece J-Track, 5/8" Termination Set, 1/2" Flat Reveal, 1/2" T&G Flat Reveal



FINISHES

Woodgrains, solid color, naturally aged metal, custom solid color matching (additional lead times apply)

ATTACHMENT

Planks: Quick-screen clips w. #10 Pan Head screws* @ 32" o.c. (standard).

 Quick-screen Clips: Included in order for 32" o.c. spacings, purchase extra for 16" o.c. spacings. For purchase (extra): 100 pcs/Bag, 1500 pcs/Box

Trims: Hard fasten w. #10 Pan Head screws* @ 16" o.c. *Screws not included.

BIM & CAD

RVT & DWG files available, see website for details



LONGBOARD

6"S

LEAD TIME

Most Popular Finishes
-ready to ship within 1 week
Additional Finishes
-ready to ship within 14 weeks

info@longboardproducts.com longboardproducts.com 800 604 0343

TECHNICAL SPECIFICATIONS

PHYSICAL DATA

6063-T5 Extruded Aluminum

100% Recyclable

Warranty: Finish:15 year (standard)/20 year* (ultra) (*10 week lead time);

Aluminum: 50 year Weight (lbs/sqft): ~1.5

6" Perforated Planks provide 21% open area

NRC/SAA	NRC	SAA
• 2 1/2" Perforated Planks w. 1" fiberglass insulation (3lbs/ft3 density)	0.70	0.72
6" Perforated Planks w. 1" fiberglass insulation (3lbs/ft3 density)	0.70	0.70
6" Perforated Planks w. SoundTex scrim	0.75	0.75
6" Perforated Planks w. 2" fiberglass insulation (3lbs/ft3 density)	0.95	0.96

TESTING

ICC-ESR 4182 Evaluation Report

 ${\sf LARR}$ - ${\sf Los}$ Angeles Department of Building Safety (LADBS) accepts ICC-ES reports as proof of compliance

Impact testing: TAS 201



Fire Rating: Class A Non-Combustible by ASTM E136 & ASTM E84; A2-s1,d0 by EN 13501-1



Light Reflectance: 5% (Black) up to 73.2% (Ultra White)